



**BRADCO**



## MINI DIRT BUCKETS

FOR COMPACT TOOL CARRIERS

The Paladin® Mini Dirt Bucket for CTC loaders is designed to handle tough conditions with ease. You can customize your bucket to suit your specific needs by incorporating optional bolt-on edge, tooth bar, and teeth. The wear-resistant high carbon cutter edge comes standard, ensuring long-lasting performance. The HD reinforcement box structures provide increased durability, while the wear bars on the underside protect against wear and tear. The 3/16" thick grade 50 steel body ensures maximum strength and reliability. Whether you're working on a landscaping project or digging trenches, this mini dirt bucket is the perfect choice for your walk behind machine.

# MINI DIRT BUCKETS

## FOR COMPACT TOOL CARRIERS

### FEATURES

- Optional Bolt on Edge, Tooth Bar, and Teeth
- Wear resistant high carbon cutter edge standard
- HD Reinforcement Box Structures for increased durability
- 3/16" thick grade 50 steel body
- Wear bars on the underside

### SPECIFICATIONS

	STANDARD DUTY						
	233282	233099	233103	233290	233284	233101	233288
WIDTH	34.5 IN.	36 IN.	42 IN.	48 IN.	36 IN.	42 IN.	48 IN.
OVERALL HEIGHT	18.1 IN.	18.1 IN.	18.1 IN.	18.1 IN.	18.1 IN.	18.1 IN.	18.1 IN.
DEPTH	30.6 IN.	30.6 IN.	30.6 IN.	30.6 IN.	30.6 IN.	30.6 IN.	30.6 IN.
RATED CAPACITY	5.8 FT <sup>3</sup>	6 FT <sup>3</sup>	7.3 FT <sup>3</sup>	8.3 FT <sup>3</sup>	6 FT <sup>3</sup>	7.3 FT <sup>3</sup>	8.3 FT <sup>3</sup>
STRUCK	4.8 FT <sup>3</sup>	5.0 FT <sup>3</sup>	5.9 FT <sup>3</sup>	6.8 FT <sup>3</sup>	5.0 FT <sup>3</sup>	5.9 FT <sup>3</sup>	6.8 FT <sup>3</sup>
BUCKET ANGLE	60°	60°	60°	60°	60°	60°	60°
WEIGHT	188 LBS	193 LBS	215 LBS	236 LBS	222 LBS	249 LBS	269 LBS
RATED OPERATING CAPACITY	1500 LBS	1500 LBS	1500 LBS	1500 LBS	1500 LBS	1500 LBS	1500 LBS
MOUNT	CII	CII	CII	CII	Bobcat	Bobcat	Bobcat
	HEAVY DUTY						
	233110	233115	233123	233263	233111	233119	
WIDTH	48 IN.	54 IN.	60 IN.	48 IN.	54 IN.	60 IN.	
OVERALL HEIGHT	18.1 IN.	18.1 IN.	18.1 IN.	18.1 IN.	18.1 IN.	18.1 IN.	
DEPTH	35.2 IN.	35.2 IN.	35.2 IN.	34.6 IN.	34.6 IN.	34.6 IN.	
RATED CAPACITY	9.3 FT <sup>3</sup>	10.5 FT <sup>3</sup>	11.8 FT <sup>3</sup>	9.3 FT <sup>3</sup>	10.5 FT <sup>3</sup>	11.8 FT <sup>3</sup>	
STRUCK	7.4 FT <sup>3</sup>	8.4 FT <sup>3</sup>	9.3 FT <sup>3</sup>	7.4 FT <sup>3</sup>	8.4 FT <sup>3</sup>	9.3 FT <sup>3</sup>	
BUCKET ANGLE	60°	60°	60°	60°	60°	60°	
WEIGHT	303 LBS	325 LBS	346 LBS	267 LBS	289 LBS	311 LBS	
RATED OPERATING CAPACITY	2500 LBS	2500 LBS	2500 LBS	2500 LBS	2500 LBS	2500 LBS	
MOUNT	SSL	SSL	SSL	CII	CII	CII	
CONSUMABLES	34.5"	36"	42"	48"	54"	60"	
BOLT ON EDGE	233093	107156	107157	107158	233268	233269	
BOLT ON TOOTH BAR KIT	119492	120712	2001065	18200	124965	236346	
BOLT ON TOOTH KIT	233266 (4 req'd)	233266 (4 req'd)	233266 (5 req'd)	233266 (5 req'd)	233266 (6 req'd)	233266 (7 req'd)	