



## Features

- Available in 84" and 96"
- Hydro-electric controlled angle and tilt, using only one loader valve
- Angle 30° right or left off center
- Tilt 10° off horizontal both directions
- Tilt indicator visible from operator's seat
- Angle and tilt cylinders are interchangeable and equipped with self-aligning bushings
- Reversible ¾" x 8" bolt-on cutting edge & formed moldboard .31" thick & 28" high
- Large 3" center pivot pin with hardened steel bushings

The **Bradco® Dozer Blade** by Paladin with tilt attach, tilts the dozer blade for more precise grading, leveling and trenching. This means you get to the next job quicker!



SPECIFICATIONS	84"	96"
Width from center line to inside edge at 15°	44"	50"
Width from center line to inside edge at 30°	43"	48"
Width at 15° angle	82"	93"
Width at 30° angle	74"	84"
Width from center line to outside edge at 15° angle	38"	44"
Width (overall)	84"	96"
Angle Left and Right	30°	30°
Tilt	10°	10°
Length (overall)	37"	37"
Height (overall)	30"	30"

## Additional Features

- Full length high carbon steel, replaceable skid shoe
- Set up to default in either tilt or angle position
- Universal skid-steer loader quick attach mounting, or use on skid-steers up to 110 HP

