



# PALADIN®

BRADCO

[www.paladinattachments.com](http://www.paladinattachments.com)



## MINI LIGHT MATERIAL BUCKETS

### FOR COMPACT TOOL CARRIERS

Our Paladin™ mini light material bucket is designed for increased durability and versatility. It features a wear-resistant high carbon cutter edge as standard, ensuring long-lasting performance. The HD reinforcement box structures further enhance its durability, making it ideal for heavy-duty applications. The wear bars on the underside provide additional protection against wear and tear, while the 3/16" thick grade 50 steel body ensures maximum strength and reliability. This mini light material bucket is the perfect choice for those looking for a high-quality bucket that can withstand even the toughest conditions.

# MINI LIGHT MATERIAL BUCKETS

## FOR COMPACT TOOL CARRIERS

### FEATURES

- Optional Bolt on Edge and Teeth
- Wear resistant high carbon cutter edge standard
- HD Reinforcement Box Structures for increased durability
- 3/16" thick grade 50 steel body
- Wear bars on the underside

### SPECIFICATIONS

	STANDARD DUTY					
	233151	233148	233157	233159	233161	233163
WIDTH	36 IN.	42 IN.	48 IN.	36 IN.	42 IN.	48 IN.
OVERALL HEIGHT	27.6 IN.	27.6 IN.	27.6 IN.	27.6 IN.	27.6 IN.	27.6 IN.
DEPTH	36.4 IN.	36.4 IN.	36.4 IN.	36.1 IN.	36.2 IN.	36.2 IN.
RATED CAPACITY	11.4 FT <sup>3</sup>	13.5 FT <sup>3</sup>	15.6 FT <sup>3</sup>	11.4 FT <sup>3</sup>	13.5 FT <sup>3</sup>	15.6 FT <sup>3</sup>
STRUCK	9.3 FT <sup>3</sup>	11 FT <sup>3</sup>	12.5 FT <sup>3</sup>	9.3 FT <sup>3</sup>	11 FT <sup>3</sup>	12.5 FT <sup>3</sup>
BUCKET ANGLE	70°	70°	70°	70°	70°	70°
WEIGHT	244 LBS	269 LBS	293 LBS	273 LBS	303 LBS	325 LBS
RATED OPERATING CAPACITY	1500 LBS	1500 LBS	1500 LBS	1500 LBS	1500 LBS	1500 LBS
MOUNT	CII	CII	CII	Bobcat	Bobcat	Bobcat

	HEAVY DUTY					
	233129	233145	233165	233167	233175	233257
WIDTH	48 IN.	54 IN.	48 IN.	54 IN.	60 IN.	68 IN.
OVERALL HEIGHT	27.6 IN.	27.6 IN.	27.6 IN.	27.6 IN.	27.6 IN.	27.6 IN.
DEPTH	36.7 IN.	36.7 IN.	36.7 IN.	36.7 IN.	39.4 IN.	39.4 IN.
RATED CAPACITY	15.6 FT <sup>3</sup>	17.6 FT <sup>3</sup>	15.6 FT <sup>3</sup>	17.6 FT <sup>3</sup>	23.3 FT <sup>3</sup>	27.1 FT <sup>3</sup>
STRUCK	12.5 FT <sup>3</sup>	14.1 FT <sup>3</sup>	12.5 FT <sup>3</sup>	14.1 FT <sup>3</sup>	18.5 FT <sup>3</sup>	21.4 FT <sup>3</sup>
BUCKET ANGLE	70°	70°	70°	70°	70°	70°
WEIGHT	313 LBS	338 LBS	350 LBS	375 LBS	435 LBS	469 LBS
RATED OPERATING CAPACITY	2500 LBS	2500 LBS	2500 LBS	2500 LBS	2500 LBS	2500 LBS
MOUNT	CII	CII	SSL	SSL	SSL	SSL

CONSUMABLES	36"	42"	48"	54"	60"	68"
BOLT ON EDGE	107156	107157	107158	233268	233269	233281
BOLT ON TOOTH KIT	233266 (4 req'd)	233266 (5 req'd)	233266 (5 req'd)	233266 (6 req'd)	233266 (7 req'd)	233266 (8 req'd)

