



Features

Sand Discharge Bucket

- Right or left discharge
- Direct hydraulic drive for conveyor
- Belt driven by cast steel sprockets
- Removable belt cover to keep weight off belt and reduce stalling

Sawdust Discharge Bucket

- Material agitator to prevent bridging
- Direct hydraulic drive for agitator versus chain and sprocket drive

FFC® Side Discharge Buckets, by Paladin®, provide the power and precision you need to lay sand, saw dust, feed and other materials for agricultural road maintenance, and sandbagging applications.



Specifications	10714-60 60" Sand	10714-72 72" Sand	10715-72 72" Sawdust	10715-84 84" Sawdust
Weight (lbs)	805	915	1120	1300
A. Width (overall)	60.0"	72.0"	72.0"	84.0"
B. Height (overall)	31.1"	31.1"	44.6"	44.6"
C. Depth (overall)	40.0"	40.0"	46.5"	46.5"
Capacity (cu. yds)	60.75	66.75	76	82
GPM Range	15-25	15-25	15-25	15-25
*Material Performance Rating				
Sand	Best	Best	Fair	Fair
Aggregate	Good	Good	Fair	Fair
Topsoil	Good	Good	Fair	Fair
Sawdust	Poor	Poor	Best	Best
Mulch	Poor	Poor	Best	Best
Silage	Fair	Fair	Good	Good

Additional Features

Sand Discharge Bucket

- 13-½" wide belt with ½" tall grouser
- Bucket edge drilled for bolt on edge
- No tool adjustment for discharge doors

Sawdust Discharge Bucket

- 15" wide belt with 1" tall grouser

