



Features

- Breaks up sod and clumps of soil
- Mixes compost and other materials
- Prepares soil for seeding or reseeding; great for small soil stabilization and landscape jobs
- Available as fixed offset with dual direct drive or adjustable offset with chain drive

FFC Tillers by Paladin, are perfect for landscaping and site preparation. They turn up hard packed ground leaving the perfect seedbed for gardens or lawns.



SPECIFICATIONS	38"	52"	68"
Order Codes	LAF3438	LAF3452	LAF3468
Weight (lbs)	435	600	695
Working Width	38"	52"	68"
Overall Width	44"	68"	78"
Number of Tines	20	28	36
GPM Range	6 to 12	12 to 40	15 to 40
PSI Range	1,500-3,000	2,000-3,500	2,300-3,500
Torque @ 2,500 PSI	470 ft-lb	939 ft-lb	939 ft-lb
Lift Capacity	<9,000 lbs	<9,000 lbs	<9,000 lbs
Operating Weight	<11,000 lbs	<11,000 lbs	<11,000 lbs

Fixed Offset, Dual Direct Drive

- Dual direct drive motors propel both ends of the tiller drive shaft for balanced torque and minimal wear and tear
- Offset tiller mounting permits work up close to walls, building and pipes, covers 76" wheel tracks
- Bi-directional shaft rotation permits under cutting and top cutting in both directions of travel
- Available in 38", 52", & 68" working widths
- 1 year warranty on structure, 6 month warranty on hydraulics



SPECIFICATIONS	52"	66"	78"
Order Codes	HT52	HT66	HT78
Weight (lbs)	750	1,000	1,300
Working Width	52"	66"	78"
Overall Width	62"	76"	88"
Number of Tines	24	32	40
Number of Scarifier Teeth (opt)	4	5	6
Recommended Hydraulics			
Motor Kit #102065	14-17 GPM	14-17 GPM	NA
Motor Kit #102066	18-28 GPM	18-28 GPM	NA
Motor Kit #102065	NA	29-44 GPM	29-44 GPM

Adjustable Offset, Chain Drive

- High torque efficient chain drive system
- Exclusive two position offset mount on 66" & 78" tiller covers wheel tracks and allows tight cut next to obstacles
- Standard dual rotation with bi-directional tines
- Scarifier assembly increases productivity by combining the tractive effort and force of the loader with the hydraulic horse power of the tiller
- Available in 52", 66", & 78" working widths
- 1 year limited warranty

