



PALADIN®

BRADCO

www.paladinattachments.com



GROUND SHARK™

EXTREME DUTY BRUSH CUTTERS FOR SKID STEERS

The Ground Shark™ Extreme Duty High Flow Brush Cutters are designed for clearing medium to heavy density brush and hardwoods up to 10" in diameter from wooded acreages, road right-of-ways, and pipeline maintenance. When the exclusive, patented retractable forward shield comes in contact with a tree, it moves up and back to expose the entire cutting edge of each blade while protecting the operator from flying debris.

GROUND SHARK™

EXTREME DUTY BRUSH CUTTERS FOR SKID STEER LOADERS

FEATURES

- Deck steps on both sides to facilitate different carriers with entry on left or right side.
- The hydraulic hoses can be easily rerouted to allow hookup to multiple machine brands.
- Exclusive patented retractable cutting forward shield. When using the Ground Shark on brush/trees that are bigger than 4" in diameter, the shield will retract on its own to allow for maximum performance.
- Serrated Edges on Push Bar and Chassis front corners enable better control when moving material.
- The motor and valve assembly are fully shielded preventing contact with debris.
- Bolt-on replaceable skid shoes.
- High torque radial piston direct drive hydraulic motor for more efficient power, improved startup and recovery.
- The Ground Shark line of brush cutters include special hydraulic valving to shut the cutter head down quickly and safely. There is a distinct audible sound during the shutdown which will indicate to the operator that the blades are coming to a stop.
- Four 3/4" thick double bevel reversible edge blades machined from AR400 high strength steel for maximum cutting power and durability.
- Multi-fastener blade retention puck mount. 3 bolts hold puck in place for blade to swivel under extreme conditions.
- Pivoting blades are installed with an alternating blade cut angle. This enables cutting action like a swinging axe which clears the previous cut.
- Bolt-on carbide stump grinding teeth increases mulching performance and take the stump down to ground level.

SPECIFICATIONS

	GS72XD			GS78XD		
OVERALL HEIGHT	30272-0022	30272-9903	30272-9925	30278-0022	30278-9903	30278-9925
OVERALL WIDTH	1/2 IN.	5/8 IN.	3/4 IN.	1/2 IN.	5/8 IN.	3/4 IN.
OVERALL HEIGHT	28.13 IN.					
OVERALL WIDTH	77.13 IN.	77.13 IN.	77.13 IN.	83.13 IN.	83.13 IN.	83.13 IN.
OVERALL LENGTH	85.59 IN.	85.59 IN.	85.59 IN.	91.62 IN.	91.62 IN.	91.62 IN.
CUTTING WIDTH	72 IN.	72 IN.	72 IN.	78 IN.	78 IN.	78 IN.
E. MINIMUM CUTTING HEIGHT	3.25* IN.					
MINIMUM STUMP GRINDING HEIGHT	.38 IN.					
CUTTING CAPACITY	10 IN.					
DECK THICKNESS	.25 IN.					
RECOMMENDED FLOW	30-45 GPM					
REQUIRED LIFT CAPACITY	2400 LBS	2400 LBS	2400 LBS	2700 LBS	2700 LBS	2700 LBS
WEIGHT	2008 LBS	2008 LBS	2008 LBS	2267 LBS	2267 LBS	2267 LBS

*Angled Front Allows Cut to Ground Level

